

**SECTION 1: Identification****1.1. Identification**

Product form	: Substance
Substance name	: Pentanoic acid, 3-methyl-, ethyl ester
CAS-No.	: 5870-68-8
Product code	: (US) V645E
Formula	: C8H16O2
Synonyms	: Ethyl-3-methyl pentanoate / Ethyl 3-methylpentanoate / Ethyl 3-methylvalerate / Ethyl 3-Methylpentanoate

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Synerzine
5340 Hwy 42 S
Ellenwood, Georgia 30294 - USA
T 404-524-6744 - F 404-577-1651
info@synerzine.com - www.synerzine.com

1.4. Emergency telephone number

Emergency number : Infotrac 1-800-535-5053 (Contract# 102471) Dial +1-352-323-3500 when outside the US

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flammable liquids Category H226 Flammable liquid and vapour
3

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS-US labeling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapour

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, hot surfaces, open flames, sparks
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P280 - Wear protective gloves, protective clothing, face protection, face shield.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P370+P378 - In case of fire: Use dry sand, alcohol resistant foam to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Pentanoic acid, 3-methyl-, ethyl ester

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name	Product identifier	%	GHS-US classification
Pentanoic acid, 3-methyl-, ethyl ester (Main constituent)	(CAS-No.) 5870-68-8	97 - 100	Flam. Liq. 3, H226

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable liquid and vapour.
- Reactivity : Flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.

Pentanoic acid, 3-methyl-, ethyl ester

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : A colorless liquid.

Color : Colorless

Odor : pineapple, fruity odor, with blueberry

Odor threshold : No data available

pH : No data available

Melting point : Not applicable

Freezing point : No data available

Boiling point : 158 °C

Flash point : 113 °F TCC

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : Not applicable.

Vapor pressure : No data available

Relative vapor density at 20 °C : No data available

Relative density : No data available

Specific gravity / density : 0.869 - 0.871 g/cm³

Molecular mass : 144.21 g/mol

Solubility : insoluble in water.

Log Pow : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, kinematic : No data available

Pentanoic acid, 3-methyl-, ethyl ester

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Pentanoic acid, 3-methyl-, ethyl ester (5870-68-8)

LD50 oral rat	> 4 g/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

Pentanoic acid, 3-methyl-, ethyl ester

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN3272 Esters, n.o.s. (Pentanoic acid, 3-methyl-, ethyl ester), 3, III
UN-No.(DOT) : UN3272
Proper Shipping Name (DOT) : Esters, n.o.s.
Pentanoic acid, 3-methyl-, ethyl ester
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

- Transport document description (IMDG) : UN 3272 ESTERS, N.O.S., 3, III
UN-No. (IMDG) : 3272
Proper Shipping Name (IMDG) : ESTERS, N.O.S.
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : III - substances presenting low danger

Pentanoic acid, 3-methyl-, ethyl ester

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 3272 Esters, n.o.s., 3, III
UN-No. (IATA) : 3272
Proper Shipping Name (IATA) : Esters, n.o.s.
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Pentanoic acid, 3-methyl-, ethyl ester (5870-68-8)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
-------------------------------------	--

15.2. International regulations

CANADA

Pentanoic acid, 3-methyl-, ethyl ester (5870-68-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Pentanoic acid, 3-methyl-, ethyl ester (5870-68-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Pentanoic acid, 3-methyl-, ethyl ester (5870-68-8)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

No additional information available


SECTION 16: Other information

Revision date : 05/26/2015

Full text of H-phrases:

H226	Flammable liquid and vapour
------	-----------------------------

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Pentanoic acid, 3-methyl-, ethyl ester

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Personal protection : G

G - Safety glasses, Gloves, Vapor respirator

Synerzine US

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product