

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/03/2015 Version: 1.0

## SECTION 1: Identification

## <u>Identification</u>

Product form : Substance Isobutyl formate Substance name CAS-No. 542-55-2 Product code : (US) W0935 Formula C5H10O2

Formate, isobutyl / Formic acid, 2-methylpropyl ester / Formic acid, isobutyl ester / 2-Synonyms

Methylpropyl formate

#### Recommended use and restrictions on use

No additional information available

#### Supplier

Synerzine 5340 Hwy 42 S

Ellenwood, Georgia 30294 - USA T 404-524-6744 - F 404-577-1651

info@synerzine.com - www.synerzine.com

#### 1.4. Emergency telephone number

: Infotrac 1-800-535-5053 (Contract# 102471) Dial +1-352-323-3500 when outside the US Emergency number

## SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

#### GHS-US classification

Flammable liquids Category H225 Highly flammable liquid and vapour

Specific target organ toxicity

H335

(single exposure) Category 3

Serious eye damage/eye H319

irritation Category 2A

May cause respiratory irritation

Causes serious eye irritation

Full text of H statements: see section 16

## GHS Label elements, including precautionary statements

## **GHS-US** labeling

Hazard pictograms (GHS-US)





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapour

H319 - Causes serious eve irritation H335 - May cause respiratory irritation

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Precautionary statements (GHS-US)

smoking. heat, hot surfaces, open flames, sparks

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P261 - Avoid breathing fume, gas, mist, spray, vapors.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear face protection, eye protection, protective gloves, protective clothing.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

06/22/2018 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P312 - Call a doctor, a POISON CENTER if you feel unwell

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use alcohol resistant foam, dry sand to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards which do not result in classification

No additional information available

## 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Name	Product identifier	%	GHS-US classification
Isobutyl formate (Main constituent)	(CAS-No.) 542-55-2	98 - 100	Flam. Liq. 2, H225 STOT SE 3, H335
			Eve Irrit. 2A, H319

Full text of hazard classes and H-statements: see section 16

#### 3.2. Mixtures

Not applicable

## SECTION 4: First-aid measures

## 4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

## 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

## 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

## 5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Reactivity : Highly flammable liquid and vapour.

## 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

06/22/2018 EN (English US) 2/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

## **Environmental precautions**

Avoid release to the environment.

## Methods and material for containment and cleaning up

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

Other information : Dispose of materials or solid residues at an authorized site.

#### Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

#### Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a wellventilated area. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

## Conditions for safe storage, including any incompatibilities

Technical measures

: Ground/bond container and receiving equipment.

Storage conditions

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

## Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls

Ensure good ventilation of the work station.

Environmental exposure controls Avoid release to the environment.

## Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

## Skin and body protection:

Wear suitable protective clothing

## Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

## SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

Physical state : Liquid

Appearance : A water-white liquid.

Color : water-white

Odor fruity sweet ethereal Odor threshold : No data available

06/22/2018 EN (English US) 3/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : 98 - 99 °C
Flash point : 50 °F TCC

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C No data available Relative density No data available Specific gravity / density  $0.88 - 0.89 \text{ g/cm}^3$ Solubility : No data available Log Pow : No data available

Auto-ignition temperature : 320 °C

Decomposition temperature : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

#### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Highly flammable liquid and vapour.

## 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

## 10.5. Incompatible materials

No additional information available

## 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Acute toxicity : Not classified
Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause respiratory irritation.

Specific target organ toxicity – repeated exposure : Not classified
Aspiration hazard : Not classified

06/22/2018 EN (English US) 4/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after eye contact : Eye irritation.

## SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

#### in the chviro

## 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapors may accumulate in the container.

#### SECTION 14: Transport information

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN2393 Isobutyl formate, 3, II

UN-No.(DOT) : UN2393

Proper Shipping Name (DOT) : Isobutyl formate

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 har at 122 F), or 130 kPa at 55 C (1.3 har at 121 F) are authorized.

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 )

CFR 175.75)

06/22/2018 EN (English US) 5/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**DOT Vessel Stowage Location** 

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number

Other information

: No supplementary information available.

#### **Transportation of Dangerous Goods**

#### Transport by sea

Transport document description (IMDG) : UN 2393 ISOBUTYL FORMATE, 3, II (5°C c.c.)

: 129

UN-No. (IMDG) : 2393

Proper Shipping Name (IMDG) : ISOBUTYL FORMATE
Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 1 L

#### Air transport

Transport document description (IATA) : UN 2393 Isobutyl formate, 3, II

UN-No. (IATA) : 2393

Proper Shipping Name (IATA) : Isobutyl formate
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

#### Isobutyl formate (542-55-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

## CANADA

#### Isobutyl formate (542-55-2)

Listed on the Canadian NDSL (Non-Domestic Substances List)

## **EU-Regulations**

#### Isobutyl formate (542-55-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

## **National regulations**

## Isobutyl formate (542-55-2)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSO (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

## 15.3. US State regulations

Isobutyl formate (542-55-2)	
State or local regulations	U.S Massachusetts - Right To Know List
	U.S New Jersey - Right to Know Hazardous Substance List
	U.S Pennsylvania - RTK (Right to Know) List

06/22/2018 EN (English US) 6/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


## SECTION 16: Other information


#### Full text of H-phrases:

Н225	Highly flammable liquid and vapour
Н319	Causes serious eye irritation
Н335	May cause respiratory irritation

	Н319	Causes serious eye irritation	
	Н335	May cause respiratory irritation	
NFPA	health hazard	: 2 - Materials that, under emergency conditions, can cause	

	temporary incapacitation of residual injury.
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
	temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even





**Hazard Rating** 

Health : 2 Moderate Hazard - Temporary or minor injury may occur

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Flammability Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

C - Safety glasses, Gloves, Synthetic apron

Synerzine US

Personal protection

Physical

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/22/2018 EN (English US) 7/7