

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/10/2015 Version: 1.0

SECTION 1: Identification

Identification

Product form : Substance 2-Methylpentanal Substance name

CAS-No. 123-15-9 Product code : (US) W1382-B Formula C6H12O

Methyl valeraldehyde / 2-Methylpentaldehyde / .alpha.-Methylvaleraldehyde / Pentanal, 2-methyl-Synonyms

/ Methylpentaldehyde / 2-Methylvaleraldehyde / Valeraldehyde, 2-methyl-

Recommended use and restrictions on use

No additional information available

Supplier

Synerzine 5340 Hwy 42 S Ellenwood, Georgia 30294 - USA T 404-524-6744 - F 404-577-1651 info@synerzine.com - www.synerzine.com

Emergency telephone number

: Infotrac 1-800-535-5053 (Contract# 102471) Dial +1-352-323-3500 when outside the US Emergency number

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS-US classification

Flammable liquids Category H225 Highly flammable liquid and vapour

Skin corrosion/irritation

H315 Causes skin irritation

Category 2

Serious eye damage/eye H319

irritation Category 2A

Specific target organ toxicity H335

(single exposure) Category 3

Hazardous to the aquatic

environment - Acute Hazard Category 3

Hazardous to the aquatic

environment - Chronic

Hazard Category 3

Full text of H statements: see section 16

Causes serious eye irritation

May cause respiratory irritation

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

2.2. GHS Label elements, including precautionary statements

H402

H412

GHS-US labeling

Hazard pictograms (GHS-US)





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation

H402 - Harmful to aquatic life

H412 - Harmful to aquatic life with long lasting effects Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. heat, hot surfaces, open flames, sparks

P233 - Keep container tightly closed.

06/22/2018 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing fume, gas, mist, spray, vapors.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear eye protection, face protection, protective clothing, protective gloves.

P302+P352 - If on skin: Wash with plenty of water

 $P303+P361+P353-If on \ skin \ (or \ hair): Take \ off immediately \ all \ contaminated \ clothing. Rinse \ skin \ with \ water/shower$

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P312 - Call a doctor, a POISON CENTER if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

 $P370 + P378 - In \ case \ of \ fire: \ Use \ alcohol \ resistant \ foam, \ dry \ sand \ to \ extinguish.$

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

| Name | Product identifier | % | GHS-US classification |
|------------------|--------------------|----------|---|
| 2-Methylpentanal | (CAS-No.) 123-15-9 | 95 - 100 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412 |

Full text of hazard classes and H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin

irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

06/22/2018 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Reactivity : Highly flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do no

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

Hygiene measures

: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Ground/bond container and receiving equipment.

Storage conditions

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-Methylpentanal (123-15-9)

Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

06/22/2018 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : A colorless liquid.

Color : colorless

Odor : Ethereal fruity odor
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available

Boiling point : 248 °F

62 °F (open cup) Flash point Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available : $0.805 - 0.815 \text{ g/cm}^3$ Specific gravity / density Molecular mass 100.16 g/mol Solubility : No data available Log Pow : No data available

Auto-ignition temperature : $199 \, ^{\circ}\text{C}$

Decomposition temperature : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

06/22/2018 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause respiratory irritation.

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

2-Methylpentanal (123-15-9)

LC50 fish 1 17.8 - 19.8 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

 $Was te treatment\ methods \\ \hspace*{0.5in} : \hspace*{0.5in} Dispose\ of\ contents/container\ in\ accordance\ with\ licensed\ collector's\ sorting\ instructions.$

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2367 alpha-Methylvaleraldehyde, 3, II

UN-No.(DOT) : UN2367

06/22/2018 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (DOT) : alpha-Methylvaleraldehyde

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 Class (DOT)

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk

packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number

Other information

: No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

: UN 2367 alpha-METHYLVALERALDEHYDE, 3, II (13°C c.c.) Transport document description (IMDG)

UN-No. (IMDG)

Proper Shipping Name (IMDG) : alpha-METHYLVALERALDEHYDE

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG)

Air transport

Transport document description (IATA) : UN 2367 Alpha-methylvaleraldehyde, 3, II

UN-No. (IATA)

Proper Shipping Name (IATA) Alpha-methylvaleraldehyde Class (IATA) : 3 - Flammable Liquids Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

2-Methylpentanal (123-15-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

06/22/2018 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Methylpentanal (123-15-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

2-Methylpentanal (123-15-9)

Listed on the Canadian DSL (Domestic Substances List)

2-Methylpentanal (123-15-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

2-Methylpentanal (123-15-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

2-Methylpentanal (123-15-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

2-Methylpentanal (123-15-9)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

2-Methylpentanal (123-15-9)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

| 2-Methylpentanal (123-15-9) | |
|-----------------------------|--|
| State or local regulations | U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List |

2-Methylpentanal (123-15-9)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

| ent of it pin about | | |
|---------------------|---|--|
| H225 | Highly flammable liquid and vapour | |
| H315 | Causes skin irritation | |
| H319 | Causes serious eye irritation | |
| H335 | May cause respiratory irritation | |
| H402 | Harmful to aquatic life | |
| H412 | Harmful to aquatic life with long lasting effects | |

06/22/2018 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| NFPA health hazard | : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. |
|----------------------|---|
| NFPA fire hazard | : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions. |
| NFPA reactivity | : 0 - Material that in themselves are normally stable, even under fire conditions. |
| NFPA specific hazard | : W - Materials that react violently or explosively with water. |
| Hazard Rating | |
| Health | : 2 Moderate Hazard - Temporary or minor injury may occur |
| Flammability | : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC) |
| Physical | : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives. |
| Personal protection | : G |

Synerzine US

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

G - Safety glasses, Gloves, Vapor respirator

06/22/2018 EN (English US) 8/8