

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/10/2015 Version: 1.0

SECTION 1: Identification

<u>Identific</u>ation

Product form : Substance

Substance name Acetic acid, 2-methylphenyl ester

CAS-No. 533-18-6 Product code : (US) W1776 Formula : C9H10O2

: Acetate, 2-methylphenyl / o-Tolyl acetate / 2-Methylphenyl acetate Synonyms

Recommended use and restrictions on use

No additional information available

Supplier

Synerzine 5340 Hwy 42 S

Ellenwood, Georgia 30294 - USA T 404-524-6744 - F 404-577-1651 info@synerzine.com - www.synerzine.com

1.4. Emergency telephone number

: Infotrac 1-800-535-5053 (Contract# 102471) Dial +1-352-323-3500 when outside the US Emergency number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category H227 Combustible liquid

Full text of H statements: see section 16

GHS Label elements, including precautionary statements

GHS-US labeling

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H227 - Combustible liquid

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. heat, hot surfaces, open flames, sparks

P280 - Wear eye protection, face protection, protective clothing, protective gloves. P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry sand to

extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

No additional information available

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

Substances

Name	Product identifier	%	GHS-US classification
Acetic acid, 2-methylphenyl ester (Main constituent)	(CAS-No.) 533-18-6	98 - 100	Flam. Liq. 4, H227

Full text of hazard classes and H-statements: see section 16

3.2. Mixtures

Not applicable

06/22/2018 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open

 $flames\ and\ other\ ignition\ sources.\ No\ smoking.\ Wear\ personal\ protective\ equipment.$

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

06/22/2018 EN (English US) 2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : A light color liquid.
Color : light color

Odor : powerful, fruity, medicinal odor

Odor threshold : No data available pH : No data available Melting point : Not applicable Freezing point : No data available

Boiling point : $208 \, ^{\circ}\text{C}$

Flash point 180 °F closed cup Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) Not applicable. Vapor pressure No data available No data available Relative vapor density at 20 °C : No data available Relative density : 1.04 - 1.05 g/ml Specific gravity / density Molecular mass 150.18 g/mol

Solubility : insoluble in water. soluble in alcohols.

Log Pow No data available No data available Auto-ignition temperature : No data available Decomposition temperature Viscosity, kinematic : No data available Viscosity, dynamic No data available **Explosion limits** No data available Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

06/22/2018 EN (English US) 3/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

: Not classified Acute toxicity Skin corrosion/irritation Not classified Serious eye damage/irritation : Not classified Respiratory or skin sensitization : Not classified : Not classified Germ cell mutagenicity Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity - single exposure : Not classified Specific target organ toxicity – repeated exposure : Not classified Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : NA1993 Combustible liquid, n.o.s., 3, III

UN-No.(DOT) : NA1993

06/22/2018 EN (English US) 4/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 Class (DOT)

Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring

a technical name

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for

UN2672).

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail

(49 CFR 173.27)

DOT Vessel Stowage Location

: 60 L

: 220 L

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Air transport

SECTION 15: Regulatory information

15.1. US Federal regulations

Acetic acid, 2-methylphenyl ester (533-18-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

Acetic acid, 2-methylphenyl ester (533-18-6)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Acetic acid, 2-methylphenyl ester (533-18-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Acetic acid, 2-methylphenyl ester (533-18-6)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

No additional information available

06/22/2018 EN (English US) 5/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Full text of H-phrases:		
H227	Combustible liquid	
NFPA health hazard	: 1 - Materials that, under emergency conditions, can cause significant irritation.	
NFPA fire hazard	: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.	
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.	
Hazard Rating		
Health	: 1 Slight Hazard - Irritation or minor reversible injury possible	
Flammability	 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA) 	
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.	
Personal protection	: B	
	B - Safety glasses, Gloves	

Synerzine US

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/22/2018 EN (English US) 6/6