

**SECTION 1: Identification****1.1. Identification**

Product form	: Substance
Substance name	: n-Butylamine
CAS-No.	: 109-73-9
Product code	: (US) W3130
Formula	: C4H11N
Synonyms	: 1-Aminobutane / Butan-1-amine / 1-Butanamine / Monobutylamine / Butylamine, n- / Butylamine, 1- / Butylamine

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Synerzine
5340 Hwy 42 S
Ellenwood, Georgia 30294 - USA
T 404-524-6744 - F 404-577-1651
info@synerzine.com - www.synerzine.com

1.4. Emergency telephone number

Emergency number : Infotrac 1-800-535-5053 (Contract# 102471) Dial +1-352-323-3500 when outside the US

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flammable liquids Category 2	H225	Highly flammable liquid and vapour
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Acute toxicity (dermal) Category 4	H312	Harmful in contact with skin
Acute toxicity (inhalation) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 1A	H314	Causes severe skin burns and eye damage
Corrosive to metals Category 1	H290	May be corrosive to metals
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS-US labeling**

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapour
H290 - May be corrosive to metals
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, hot surfaces, open flames, sparks
P233 - Keep container tightly closed.
P234 - Keep only in original container.

n-Butylamine

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe fume, gas, mist, spray, vapors.
P261 - Avoid breathing fume, gas, mist, spray, vapors.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P312 - If swallowed: Call a doctor, a POISON CENTER if you feel unwell
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a doctor, a POISON CENTER
P312 - Call a doctor, a POISON CENTER if you feel unwell
P321 - Specific treatment (see supplemental first aid instructions on this label)
P330 - Rinse mouth.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use alcohol resistant foam, dry sand to extinguish.
P390 - Absorb spillage to prevent material-damage.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P406 - Store in corrosive resistant container with a resistant inner liner.
P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name	Product identifier	%	GHS-US classification
n-Butylamine (Main constituent)	(CAS-No.) 109-73-9	99 - 100	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Met. Corr. 1, H290 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns.
Symptoms/effects after eye contact : Serious damage to eyes.

n-Butylamine

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Reactivity : Highly flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Avoid contact with skin, eyes and clothing. Do not breathe fume, gas, mist, spray, vapors.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Do not breathe fume, gas, mist, spray, vapors.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up.

Incompatible materials : Metals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

n-Butylamine (109-73-9)		
ACGIH	Local name	n-Butylamine
ACGIH	ACGIH Ceiling (ppm)	5 ppm
ACGIH	Remark (ACGIH)	URT & eye irr

n-Butylamine

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Butylamine (109-73-9)		
OSHA	OSHA PEL (Ceiling) (mg/m ³)	15 mg/m ³
OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm
OSHA	Limit value category (OSHA)	prevent or reduce skin absorption
IDLH	US IDLH (ppm)	300 ppm
NIOSH	NIOSH REL (ceiling) (mg/m ³)	15 mg/m ³
NIOSH	NIOSH REL (ceiling) (ppm)	5 ppm
NIOSH	US-NIOSH chemical category	Potential for dermal absorption

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : A clear colorless to yellow liquid.
Color : colorless to yellow
Odor : ammonia-like fishy
Odor threshold : No data available
pH : No data available
Melting point : -50 °C
Freezing point : No data available
Boiling point : 78 °C
Flash point : 19 °F TCC
Relative evaporation rate (butyl acetate=1) : 7.3
Flammability (solid, gas) : Not applicable.
Vapor pressure : 93 hPa (at 20 °C)
Relative vapor density at 20 °C : No data available
Relative density : No data available
Specific gravity / density : 0.738 g/cm³ (at 20 °C)
Solubility : No data available
Log Pow : 0.97
Auto-ignition temperature : 290 °C
Decomposition temperature : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

n-Butylamine

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

n-Butylamine (109-73-9)	
LD50 oral rat	366 mg/kg
LD50 dermal rabbit	850 µl/kg
LC50 inhalation rat (ppm)	2000 - 4000 ppm/4h
ATE US (oral)	366 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	2000 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

n-Butylamine (109-73-9)	
LC50 fish 1	268 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

n-Butylamine

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Butylamine (109-73-9)

LC50 fish 2	32 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
-------------	---

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

n-Butylamine (109-73-9)

Log Pow	0.97
---------	------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1125 n-Butylamine, 3, II
UN-No.(DOT)	: UN1125
Proper Shipping Name (DOT)	: n-Butylamine
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 3 - Flammable liquid 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 5 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Emergency Response Guide (ERG) Number	: 132

n-Butylamine

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Transport document description (IMDG) : UN 1125 n-BUTYLAMINE, 3 (8), II (-9°C c.c.)
UN-No. (IMDG) : 1125
Proper Shipping Name (IMDG) : n-BUTYLAMINE
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger
Subsidiary risks (IMDG) : 8 - Corrosive substances
Limited quantities (IMDG) : 1 L

Air transport

Transport document description (IATA) : UN 1125 n-Butylamine, 3 (8), II
UN-No. (IATA) : 1125
Proper Shipping Name (IATA) : n-Butylamine
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger
Subsidiary risks (IATA) : 8 - Corrosive substances

SECTION 15: Regulatory information

15.1. US Federal regulations

n-Butylamine (109-73-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

n-Butylamine (109-73-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

n-Butylamine (109-73-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

n-Butylamine (109-73-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

n-Butylamine (109-73-9)

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
----------------------------	--

n-Butylamine

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H290	May be corrosive to metals
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H332	Harmful if inhaled

NFPA health hazard


: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection

: C

C - Safety glasses, Gloves, Synthetic apron

Synerzine US

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product